

## DC Hose Reel

DC Hose Reel 38/50 is the second generation of our spring operated hose reel and is a complete redesign. Due to its smooth operation the DC Hose Reel 38/50 is very user friendly. Simply pull down the hose and it locks in the desired position. Pull it again and the hose rewinds to the starting position.

The sealed drum guarantees smooth operation and protects the hose from every day wear and tear. The DC Hose Reel 38/50 can be installed either on the ceiling (Part No 7503, 7506) or on the wall (Part No 7504, 7505).

DC Hose Reel 38/50 is more sturdy than its predecessor and has a longer reach and a wider radius of action due to the extended hose. Hence the sealed drum is not pivotal anymore and mounted in a fixed position instead.

*Part No 7503 Hose Reel 38 mm, complete, ceiling*

*Part No 7504 Hose Reel 38 mm, complete, wall*

*Part No 7505 Hose Reel 50 mm, complete, wall*

*Part No 7506 Hose Reel 50 mm, complete, ceiling*



TECHNICAL DATA	38 mm	50 mm
Hose Part No/length, antistatic	2013/8 m/26 ft., Ø 50 mm/2 in. + 2012/2 m/6 ft., Ø 38mm/1.5 in.	2013/10 m Ø 50 mm/2 in.
Connection diameter	Ø 50 mm/2 in.	Ø 50 mm/2 in.
Compressed air supply	min 5 bar (75 psi)	min 5 bar (75 psi)
Recommended air-flow	100-150 m <sup>3</sup> /h	150-520 m <sup>3</sup> /h