

Large Capacity Dual Hose Reels

1275 Series

1275 Series "Dual Hose" hand crank or motorized hose reels are designed for large capacity applications. This series features dual plumbing with two swivel inlets and two low profile outlets that compliment the open drum slot and provide a non-crimping, flat smooth hose wrap. The industry preferred one piece all welded "A" frame design adds rigidity and strength while the positive gear drive rewind assures consistent trouble-free performance.

1275 SERIES Offers...

- ✓ Two Solid Brass BS Swivels & Two Outlet Risers For Dual Hose Applications
- ✓ One Piece All Welded Steel "A" Frame Construction
- ✓ Low Profile Riser & Open Drum Slot For Smooth, Even Hose Wraps
- ✓ Permanently Lub. Pillow Block Bearings Assure Smooth Rotation
- ✓ Swivel O-Ring Seals, Supported By Teflon® Spacers



MOTOR

MANUAL

SPRING

Drive Type

Manual

Motor

Media

Air

Water

Oil

Swivel material

Steel

Seal material

Nitrile



1275 HAND CRANK MODELS // Air & Water, oil & fuel

MODEL no hose	I.D.	O.D.	Length	I.D.*	O.D.*	Length*	BAR	Inlet	Outlet	KG	Size
1275-4-50	12mm	21mm	15 m	10mm	17mm	21 m	210	1/2"	1/2"	18	1
1275-4-100	12mm	21mm	30 m	10mm	17mm	42 m	210	1/2"	1/2"	19	2
1275-4-150	12mm	21mm	45 m	10mm	17mm	61 m	210	1/2"	1/2"	21	3
1275-4-200	12mm	21mm	61 m	10mm	17mm	91 m	210	1/2"	1/2"	25	4
1275-6-50	25mm	37mm	15 m	19mm	29mm	18 m	210	1"	1"	29	5
1275-6-75	25mm	37mm	23 m	19mm	29mm	33 m	210	1"	1"	31	6
1275-6-100	25mm	37mm	30 m	19mm	29mm	47 m	210	1"	1"	34	7
1275-6-150	25mm	37mm	45 m	19mm	29mm	61 m	210	1"	1"	40	8

MOTORS DRIVEN MODELS // Add the suffix to hand crank models above

Suffix #	Motor Type	Description	Extra KG
A	AIR #4 GAST	Comp. Air Motor	4
E	ELECTRIC - 12V DC	1/3 HP	6
EB	ELECTRIC - 24V DC	1/2 HP	12
ED	ELECTRIC Explosion Proof	1/2 HP	12
EA	ELECTRIC Explosion Proof - 115V DC	1/2 HP	12
H	HYDRAULIC	End Ported 9/16-18 UNF	3
C	CRANK	Bevel Gear	2

Also available in
STAINLESS STEEL
Please see page 20 & 21



DIMENSIONS

SIZE	A	B	C	D	Crank E	Elec E	Air E	F	G
1	159	203	445	340	490	543	495	385	476
2	159	305	445	441	592	644	597	385	476
3	159	457	445	594	745	797	750	385	476
4	159	610	445	746	897	950	900	385	476
5	267	343	508	484	-	770	720	480	273
6	267	343	610	484	-	770	720	518	664
7	267	508	610	650	-	785	885	518	664
8	267	508	711	650	-	785	885	573	764

