

EN Series

EN Series “Enclosed” spring driven hose reels are protected by a powder coated steel casing that shields out the elements to protect and extend the life of the reel, the hose and the components inside. It adds a neat, tidy, aesthetic appearance to work environments that demand a clean and professional look. The 3 piece casing is easy to assemble and disassemble for simple installation and maintenance.

EN SERIES Offers...

- ✓ Improved Appearance & Greater Protection
- ✓ Designed For Easy Installation & Service
- ✓ Heavy Gauge Steel 3-Piece Casing
- ✓ Adjustable Hose Roller Guide
- ✓ “Super Hub” Dual Axle Support On Models With Size Index #2



MOTOR

MANUAL

SPRING

Drive Type **Spring**

Media **Air**

Water

Oil

Grease

Swivel material **Brass**

Seal material **Nitrile**

Also available in **STAINLESS STEEL**
Please see page 20 & 21

LOW PRESSURE // Air & Water

MODEL hose	MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
EN-N-125-BGX	ENL-N-125-BGX	6mm	12mm	8 m	21	1/4"	1/4"	23	22	1
EN-N-150-BGX	ENL-N-150-BGX	6mm	12mm	15 m	21	1/4"	1/4"	24	21	1
EN-N-325-BGX	ENL-N-325-BGX	10mm	17mm	8 m	21	3/8"	3/8"	22	21	1
EN-N-350-BGX	ENL-N-350-BGX	10mm	17mm	15 m	21	3/8"	3/8"	30	26	2
EN-N-425-BGX	ENL-N-425-BGX	12mm	21mm	8 m	21	1/2"	1/2"	29	26	1
EN-N-450-BGX	ENL-N-450-BGX	12mm	21mm	15 m	21	1/2"	1/2"	31	28	2

Maximum temp. 65°C Reels without hose can be used for air, water & oil

MEDIUM PRESSURE // Air, Water & Oil

MODEL hose	MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
ENM-N-325-BGX	ENML-N-325-BGX	10mm	17mm	8 m	210	3/8"	3/8"	28	25	1
ENM-N-350-BGX	ENML-N-350-BGX	10mm	17mm	15 m	210	3/8"	3/8"	36	31	2
ENM-N-425-BGX	ENML-N-425-BGX	12mm	21mm	8 m	175	1/2"	1/2"	28	25	1
ENM-N-450-BGX	ENML-N-450-BGX	12mm	21mm	15 m	175	1/2"	1/2"	37	32	2

Reels with hose come with one wire braid hose suitable for air, water & oil with a maximum temp. 99°C

HIGH PRESSURE // Air, Water, Oil & Grease

MODEL hose	MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
ENH-N-150-BGX	ENHL-N-150-BGX	6mm	12mm	15 m	350	1/4"	1/4"	36	31	2
ENH-N-160-BGX	ENHL-N-160-BGX	6mm	12mm	18 m	350	1/4"	1/4"	39	32	2
ENH-N-350-BGX	ENHL-N-350-BGX	10mm	17mm	15 m	280	3/8"	3/8"	36	31	2

Maximum temp. 99°C

DIMENSIONS

SIZE	A	B	C	D	E	L	M
1	179	476	476	152	152	102	127
2	235	552	552	152	152	102	127

